

TOPAZ

Anti-Slip Gloss Restorer



Scan for product's
Material Safety Data Sheet

FEATURES

- One step cleaner/maintainer
- Repairs scuffs and improves gloss
- Highly concentrated
- Improves traction

BENEFITS

- Time and labor cost savings
- Keeps floors looking great
- Low end use cost
- Less exposure to slip and falls

AREAS OF USE:

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Quarry Tile
- Concrete

DIRECTIONS:

This product must be diluted before use. See your supervisor or technical sales representative for instructions on dispenser use.

Dispense diluted product into a mop bucket or auto-scrubber. Dust mop all flooring and remove gum and adhesives. Apply a thin, even coat on the surface. Do not pickup solution. Allow to dry thoroughly. Burnish all flooring to restore the floor to the ultimate "wet look" shine with a burnishing pad.

NOTE: Don't allow restorer solution to remain in the auto-scrubber tank. Drain and rinse.

CAUTION

EYE IRRITANT. MAY CAUSE SKIN IRRITATION WITH PROLONGED CONTACT. Avoid contact with skin, eyes and clothing. Wear protective footwear when applying to floor. Floors are slippery when wet; keep all unauthorized persons away. Do not take internally. Wear rubber gloves when handling. Wash thoroughly with soap and water after handling. Keep out of reach of children.

FIRST AID

EYE CONTACT: Immediately flush with water for 15 minutes. If irritation persists, seek medical attention.

SKIN CONTACT: Flush with water followed by washing with mild soap and water. Remove contaminated clothing and launder before reuse. Seek medical attention if irritation develops.

INGESTION: Call physician immediately.

CONTAINS

Acrylate Copolymer Dispersion (63744-68-3), Polyethylene Glycol (25322-68-3), Dipropylene Glycol Methyl Ether (34590-94-8), NonIonic Surfactant (9016-45-9), Dye (N/A), Perfume Oils (N/A), Water (7732-18-5).

SPECIFICATIONS:

Color:
Opaque orange

Odor:
Citrus/lime

pH (Conc):
8.5 – 9.0

pH (RTU):
7.0 – 7.5

Fixed Dilution:
1:64

Ounces Per Gallon:
2.0

Gallon Yield/Bottle:
41

Viscosity:
Water Thin

Slip Resistance:
Increases with regular use

Flash Point:
None

Solubility:
Complete with water

Detergency:
Excellent

VOC Content:
10%

Storage/Stability:
1 year

Weight Per Gallon:
8.69 lbs./gal

Freeze/Thaw Stability:
Keep from freezing

FOR USE IN
PrecisionFLO
DILUTION CONTROL SYSTEMS ONLY

MISCO

1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com

HEALTH		1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		A



6 TOPAZ^{PF}

Anti-Slip Gloss Restorer

Restaurador Anti-Slip Del Lustre



Availability:

Packaging	Item #
2-80 oz.:	115905

Vinyl Tile
Azulejo del vinilo

Linoleum
Linóleo

Terrazzo
Terrazo

Quarry Tile
Azulejo de la mina

Concrete
Hormigón

DESCRIPTION

An ideal companion product for use with any high speed maintenance program. Regular use of this product keeps floors looking great day after day. Special proprietary ingredients bond to the surface of the floor to create an anti-slip surface, making it ideally suited for nursing homes, supermarkets, hospitals, schools and other public areas. This product effectively cleans the floor and restores floor finish. Highly concentrated for economical use dilutions, it can be mopped on or used through an automatic scrubber. Once the product dries to a haze, use a high speed burnisher to “pop” the gloss to a brilliant shine.



1048 Stinson Drive, Reading PA 19605
Phone: 1-800-548-4568

www.miscoproducts.com